

TCE Worldwide Web Services API 1.1.0 OAS3

<http://tceorder.ro/api/openapi.json>

The latest version of this API can be found and tested at <http://tceorder.ro/api>

This API implements a standard [REST](#) architecture.

The authentication method is [HTTP Basic access](#).

It is recommended to request a separate username/password for automated integrations than the ones used to access the web user interface.

The content types supported are [JSON](#) (fully) and [XML](#) (experimentally).

All methods return appropriate [HTTP status codes](#) for error checking.

Preliminary testing can be done on the [SwaggerHub Mocking](#) endpoint.

Any test orders submitted to the [Production](#) server must be marked as such and deleted soon after a successful submission.

Please contact us if you require additional information.

[TCE WWS - Website](#)

[Send email to TCE WWS](#)

Servers

<http://tceorder.ro/api/v1> - Production

Authorize



orders



POST /orders Create an order.



Parameters

Try it out

No parameters

Request body

application/json

Example Value Schema


```
{
  "payer_name": "TCE WORLDWIDE SERVICES SRL",
  "payer_country": "Romania",
  "payer_county": "Bucuresti",
  "payer_locality": "Bucuresti",
  "payer_address": "Drumul Săbăreni nr. 24-26",
  "payer_code": "060647",
  "payer_contact": "",
  "payer_phone": "031 9668",
  "sender_name": "TCE WORLDWIDE SERVICES SRL",
  "sender_country": "Romania",
  "sender_county": "Bucuresti",
  "sender_locality": "Bucuresti",
```

```
"sender_address": "Drumul Săbăreni nr. 24-26",
"sender_code": "060647",
"sender_contact": "",
"sender_phone": "031 9668",
"consignee_name": "TCE LOGISTIK HUNGARY KFT",
"consignee_country": "Ungaria",
"consignee_county": "Budapest",
"consignee_locality": "Budapest",
"consignee_address": "Szikrataviró ut. 17-21",
"consignee_code": "1211",
"consignee_contact": "",
"consignee_phone": "+40 314 344 228",
"pickup_date": "2019-01-30",
"dropoff_date": "2019-01-31",
"item_type": "pallet",
"item_count": 1,
"item_weight": 100,
"item_length": 120,
"item_width": 80,
"item_height": 60,
"item_value": 1000,
"item_description": "Goods",
"service_type": "courier",
"repayment_value": 100,
"repayment_currency_id": "EUR",
"payment_method": "pickup",
"has_return_documents": false,
"has_saturday_delivery": true,
"has_receipt_acknowledgement": true,
"has_package_verification": false,
"has_advance_notice": false,
"sender_reference": "1234567890",
"notes": "TEST API"
}
```

Responses

Code	Description	Links
201	<i>Created</i>	<i>No links</i>
	<div style="border: 1px solid green; padding: 2px; display: inline-block;">application/json</div> <p>Controls Accept header.</p> <p>Example Value Schema</p> <pre>[{ "id": 1234567 }]</pre>	
401	<i>Unauthorized</i>	<i>No links</i>
403	<i>Forbidden</i>	<i>No links</i>

Code	Description	Links
422	<p><i>Unprocessable Entity</i></p> <p><code>application/json</code></p> <p>Example Value Schema</p> <pre>{ "status": 422, "meta": ["pickup_date", "dropoff_date"] }</pre>	No links
500	<p><i>Internal Server Error</i></p>	No links

GET `/orders/{id}` Retrieve an order. 

Parameters [Try it out](#)


Name	Description
id * required integer (path)	Order ID

Responses

Code	Description	Links
------	-------------	-------

Code	Description	Links
200	<p><i>OK</i></p> <p>application/json</p> <p>Controls Accept header.</p> <p>Example Value Schema</p> <pre>[{ "id": 1234567, "payer_name": "TCE WORLDWIDE SERVICES SRL", "payer_country": "Romania", "payer_county": "Bucuresti", "payer_locality": "Bucuresti", "payer_address": "Drumul Săbăreni nr. 24-26", "payer_code": "060647", "payer_contact": "", "payer_phone": "031 9668", "sender_name": "TCE WORLDWIDE SERVICES SRL", "sender_country": "Romania", "sender_county": "Bucuresti", "sender_locality": "Bucuresti", "sender_address": "Drumul Săbăreni nr. 24-26", "sender_code": "060647", "sender_contact": "", "sender_phone": "031 9668", "consignee_name": "TCE LOGISTIK HUNGARY KFT", "consignee_country": "Ungaria", "consignee_county": "Budapest", "consignee_locality": "Budapest", "consignee_address": "Szikrataviro ut. 17-21", "consignee_code": "1211", "consignee_contact": "", "consignee_phone": "+40 314 344 228", "pickup_date": "2019-01-30", "dropoff_date": "2019-01-31", "item_type": "pallet", "item_count": 1, "item_weight": 100, "item_length": 120, "item_width": 80, "item_height": 60, "item_value": 1000, "item_description": "Goods", "service_type": "courier", "repayment_value": 100, "repayment_currency_id": "EUR", "payment_method": "pickup", "has_return_documents": false, "has_saturday_delivery": true, "has_receipt_acknowledgement": true, "has_package_verification": false, "has_advance_notice": false, "sender_reference": "1234567890", "notes": "TEST API", "status": 0, "status_date": "2019-01-31", "status_time": "12:00", "status_name": "", "status_info": "" }]</pre>	<i>No links</i>
403	<i>Forbidden</i>	<i>No links</i>
404	<i>Not Found</i>	<i>No links</i>

Code	Description	Links
500	<i>Internal Server Error</i>	<i>No links</i>


DELETE `/orders/{id}` Delete an order. 

Parameters Try it out

Name	Description
id * required integer (path)	Order ID

Responses

Code	Description	Links
204	<i>No Content</i>	<i>No links</i>
401	<i>Unauthorized</i>	<i>No links</i>
403	<i>Forbidden</i>	<i>No links</i>
404	<i>Not Found</i>	<i>No links</i>
500	<i>Internal Server Error</i>	<i>No links</i>

GET `/labels/{id}` Retrieve an order's transport documents (PDF). 

Parameters Try it out

Name	Description
id * required integer (path)	Order ID

Responses

Code	Description	Links
200	<i>OK</i> application/pdf Controls Accept header. Example Value Schema string	<i>No links</i>
403	<i>Forbidden</i>	<i>No links</i>
404	<i>Not Found</i>	<i>No links</i>
500	<i>Internal Server Error</i>	<i>No links</i>

Schemas

```
Order {
  id string
  payer_name* string
  payer_country* string
  payer_county string
  payer_locality* string
  payer_address* string
  payer_code* string
}
```

string
example: 1234567
readOnly: true

ID

string
example: TCE WORLDWIDE SERVICES SRL

Nume plătitor

string
example: Romania

Țară plătitor

string
example: Bucuresti

Județ plătitor

string
example: Bucuresti

Localitate plătitor

string
example: Drumul Săbăreni nr. 24-26

Adresă plătitor

string
example: 060647

	Cod poștal plătitor
payer_contact	string example:
	Persoană contact plătitor
payer_phone	string example: 031 9668
	Telefon plătitor
sender_name*	string example: TCE WORLDWIDE SERVICES SRL
	Nume expeditor
sender_country*	string example: Romania
	Țară expeditor
sender_county	string example: Bucuresti
	Județ expeditor
sender_locality*	string example: Bucuresti
	Localitate expeditor
sender_address*	string example: Drumul Săbăreni nr. 24-26
	Adresă expeditor
sender_code*	string example: 060647
	Cod poștal expeditor
sender_contact	string example:
	Persoană contact expeditor
sender_phone	string example: 031 9668
	Telefon expeditor
consignee_name*	string example: TCE LOGISTIK HUNGARY KFT
	Nume destinatar
consignee_country*	string example: Ungaria
	Țară destinatar
consignee_county	string example: Budapest
	Județ destinatar
consignee_locality*	string example: Budapest
	Localitate destinatar
consignee_address*	string example: Szikrataviró ut. 17-21
	Adresă destinatar
consignee_code*	string example: 1211
	Cod poștal destinatar
consignee_contact	string example:

	Persoană contact destinatar
consignee_phone	string example: +40 314 344 228
	Telefon destinatar
pickup_date*	string(\$date) example: 2019-01-30
	Data preluare
dropoff_date*	string(\$date) example: 2019-01-31
	Data livrare
item_type*	string example: pallet
	Tip itemuri
	Enum:
	[envelope, parcel, pallet, ltl, ftl]
item_count*	integer(\$int32) minimum: 1 example: 1
	Număr itemuri
item_weight*	number(\$decimal) minimum: 0.1 example: 100
	Greutate itemuri (kg)
item_length*	number(\$decimal) example: 120
	Lungime palet (cm)
item_width*	number(\$decimal) example: 80
	Lățime palet (cm)
item_height*	number(\$decimal) example: 60
	Înălțime palet (cm)
item_value*	number(\$decimal) example: 1000
	Valoare declarată (EUR)
item_description	string example: Goods
	Descriere itemuri
service_type*	string example: courier
	Tip serviciu
	Enum:
	[courier, cargo]
repayment_value	number(\$decimal) example: 100
	Valoare ramburs
repayment_currency_id	string example: EUR
	Monedă ramburs
	Enum:
	[BGN, CZK, EUR, HUF, PLN, RON]
payment_method*	string example: pickup
	Modalitate plată


```

modulitate plata
Enum:
    [ pickup, contract, prepay, order ]
has_return_documents boolean
example: false
Serviciu retur documente

has_saturday_delivery boolean
example: true
Serviciu livrare sâmbătă

has_receipt_acknowledgement boolean
example: true
Serviciu confirmare primire

has_package_verification boolean
example: false
Serviciu verificare colet

has_advance_notice boolean
example: false
Serviciu preavizare livrare

sender_reference string
example: 1234567890
Referință client

notes string
example: TEST API
Observații client

status number($int32)
readOnly: true
example: 0
Statut curent:
    • 0 = Înregistrată
    • 10 = Preluată
    • 11 = Anulată
    • 12 = Refuzată la preluare
    • 13 = Colet nepreluat
    • 14 = Colet deteriorat
    • 20 = Transit domestic
    • 21 = Checkpoint ARD
    • 30 = Transit internațional
    • 31 = Checkpoint BUD
    • 40 = În livrare
    • 41 = Refuzată la destinatar
    • 42 = În așteptare informații
    • 43 = Retur la expeditor
    • 44 = Adresă greșită
    • 45 = Livrare eșuată
    • 47 = Client negăsit la adresă
    • 48 = Livrare reprogramată
    • 49 = Livrare parțială
    • 50 = Livrată
    • 55 = Stornare

Enum:
    [ 0, 10, 11, 12, 13, 14, 20, 21, 30, 31, 40, 41, 42, 43, 44, 45, 47, 48, 49,
50, 55 ]
status_date string($date)
readOnly: true
example: 2019-01-31
Dată statut final

status_time string
readOnly: true
example: 12:00
Oră statut final

status_name string
readOnly: true

```

```
        readOnly: true
        example:
            Persoană statut final
    status_info
        string
        readOnly: true
        example:
            Informații statut
    }
```

```
Error {
    status      string
               Statut
    meta        [...]
}
```